DA-12

18 Gbps 1x2 HDMI Splitter

FEATURE:

- Up to 4K2K@60Hz with 24bit RGB/YCBCR 4:4:4
- VESA format up to QSXGA@60Hz
- Supports LPCM 7.1CH, Dolby TrueHD, and DTS-HD Master Audio
- Built-in equalizer, retiming and driver
- Smart EDID, STD (1080p) mode and TV (copy OUT1) mode
- Compact design for an easy and flexible installation

DA-12

1x2 HDMI 18 Gbps Splitter is an advanced solution for splitting a HDMI content to 2 HDMI outputs synchronously. It provides high performance audio and video up to 4K2K@60Hz (4:4:4) and is capable of receiving, retiming and transmitting up to 18Gbps of bandwidth with no data loss.

Splitter

18 Gbps 1x2 HDMI Splitter

DA-12 18 Gbps 1x2 HDMI Splitter

SPECIFICATIONS:

Technical

Video Bandwidth	600MHz/18 Gbps
Input Port	1xHDMI Type A (19-pin female)
Output Ports	2xHDMI Type A (19-pin female)
Video Resolution	4K2K@24/25/30/60Hz
ESD Protection	Human body model—±8kV (Air-gap discharge) &±4kV (Contact discharge)

Mechanical

Chassis Material	Metal
Silkscreen Color	Black
Dimensions	56 mm(W)x100 mm(D)x16mm(H)
Weight	165g
Power Supply	Input: AC100 – 240V 50/60Hz, Output: DC 5V/1A
	(US/EU standards, CE/FCC/UL certified)
Power Consumption	2W
Operation Temperature	32°F – 104°F / 0°C – 40°C
Storage temperature	–4°F – 140°F / –20°C – 60°C
Relative Humidity	20 – 90% RH (no condensation)

Splitter