

# EX-HDBT-40-WP-USBC

HDMI/USB-C 4K 18 Gbps Wall Plate  
40m with USB (US 1-Gang)

## FEATURE:

- Compliant with HDMI 2.0b, HDCP 2.2 and Display Port 1.2a
- HDMI input supports 18Gbps video bandwidth; USB-C input supports 5.4Gbps video bandwidth
- Video resolution up to 4K2K@50/60Hz 4:4:4
- HDBaseT output can extend video transmission distance up to 230ft / 70m for 1080P@60 or 131ft / 40m for 4K@60 via a single CAT6/6a/7 cable
- Support 3D, HDR10 and Dolby Vision
- HDMI audio formats support LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD
- Support HDMI and USB-C input
- With USB-C charging port
- US one-gang enclosure for Decora-style wall plate openings
- Input signal selection supports automatic mode and manual mode
- Support POE function (only from Receiver to Transmitter)
- Available in white or black coating



## EX-HDBT-40-WP-USBC

The wall plate is a 2x1 switcher and HDBaseT transmitter with HDMI and USB-C inputs. It features a US one-gang enclosure for Decora-style wall plate openings with interchangeable black and white wall plates and faceplates. Support video resolution up to 4K2K@50/60Hz 4:4:4. It supports bidirectional RS-232 pass-through, and the RS-232 control signal can be transmitted up to 131ft / 40m. The product is remotely powered by the receiver or other HDBaseT-equipped devices via POE.



# Extender

HDMI/USB-C 4K 18 Gbps Wall Plate  
40m with USB (US 1-Gang)



## EX-HDBT-40-WP- USBC

HDMI/USB-C 4K 18 Gbps Wall Plate  
40m with USB (US 1-Gang)

### SPECIFICATIONS:

#### Technical

HDMI Compliance	HDMI 2.0b
HDCP Compliance	HDCP 2.2
DP Compliance	Display Port 1.2a
Video Bandwidth	USB-C: 5.4 Gbps HDMI: 18 Gbps
Video Resolution	480i-1080p50/60Hz, 4Kx2K@24/30Hz, 4k2k@60Hz
Color Space	RGB, YCbCr 4:4:4 / 4:2:2, YUV 4:2:0
Color Depth	8/10/12-bit (1080P@60Hz) 8-bit (4K@60Hz)
HDR	Support
HDMI Audio Formats	LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD
Transmission Distance	Max distance (1080P) : 230ft / 70m over CAT6/6a/7 Max distance (4K): 131ft / 40m over CAT6/6a/7
ESD Protection	Human body model — ±8kV (Air-gap discharge) &±4kV (Contact discharge)

#### Connections

##### Transmitter

Input	1x HDMI IN [Type A, 19-pin female] 1 x USB-C
Output	1 x HDBaseT Out [RJ45, 8-pin female] 1x USB-C (only for charging)
Control	1x RS-232 [3-pin phoenix connector] 1x FW [Micro USB, Update port]

##### Receiver

Input	1x HDMI IN [Type A, 19-pin female] 1x HDBaseT IN [RJ45, 8-pin female]
Output	1x HDMI OUT [Type A, 19-pin female] 1x AUDIO OUT [Phoenix jack]
Control	1x RS-232 [3-pin phoenix connector] 1x FW [Micro USB, Update port]

#### Mechanical

Housing	Metal Enclosure
Color	White / Black
Dimensions	Wall plate: 33.3mm [W] x 65.7mm [D] x 68.7mm [H] Faceplate: 69.9mm [W] x 3mm [D] x 114.3mm [H] Receiver: 200mm [W] x 102.8mm [D] x 22mm [H]
Weight	Wall plate: 197g, Receiver: 517g
Power Supply	POE (only from Receiver to Transmitter)
Power Consumption	Wall plate: 7.92W (Max), Receiver: 6W (Max)
Operation Temperature	32°F - 104°F / 0°C - 40°C
Storage temperature	-4°F - 140°F / -20°C - 60°C
Relative Humidity	20 - 90% RH (no condensation)