

# SW-2-KVM

## KVM Switcher 2 ports

### FEATURE:

- HDCP 2.3 compliant
- Support Ultra-Wide Screen, resolution up to 4K@60Hz, 2K@60Hz/144Hz as specified in HDMI 2.1
- HDR, HDR10, HDR10+, Dolby Vision, HLG pass-through
- Using only 1 set of keyboard, mouse and monitor to control 2 computers
- Support video fast switching, and keyboard/mouse seamless switching
- Each input port has an EDID emulator to provide the correct information for the PC
- Support hot plug, disconnect or connect devices to the KVM at any time
- Switching via front panel buttons, keyboard/mouse hotkeys, IR remote control, and RS-232 commands
- Support auto switching
- Advanced hardware/software design and production ensure zero latency
- The integrated USB 3.0 ports allow you to share USB peripherals like printer, scanner, webcam and hard disk between computers with data transfer rate up to 5Gbps
- Compact design for easy and flexible installation



### SW-2-KVM

This is a 2x1 KVM Switcher with hotkey switching. It supports resolutions up to 4K@60Hz 4:4:4 8bit and can also transmit USB 3.0 signal up to 5Gbps for KVM function. The switcher features virtual interaction function, so that it can automatically wake up the connected PC that is in standby mode, which can reduce the switching time. It also supports direct switching through buttons on the front panel, IR remote, and hotkey through keyboard/mouse connected to the special USB port. It provides a wide compatibility choice for different operating systems, such as Windows, Mac OS and Linux, no driver required and simple plug and play.



Audio  
Visual  
Equipment

# Switchers

KVM Switcher 2 ports

**SPECIFICATIONS:****Technical**

HDMI Compliance	HDMI 2.0
HDCP Compliance	HDCP 2.3
Video Bandwidth	18Gbps
Audio Latency	No Latency
Video Latency	No Latency
Video Resolution	Up to 4K@60Hz, 2K@60Hz/144Hz
IR Level	5Vp-p
IR Frequency	Fixed frequency 38KHz
Color Space	RGB, YCbCr 4:4:4, YCbCr 4:2:2, YCbCr 4:2:0
Color Depth	8/10/12bit
HDR	HDR, HDR10, HDR10+, Dolby Vision, HLG
CEC	Support
Audio Formats	<b>HDMI IN/OUT:</b> LPCM, Dolby Digital/Plus/EX, Dolby True HD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DTS:X, DSD <b>L/R OUT:</b> PCM 2.0CH
ESD Protection	IEC 61000-4-2: ±8kV (Air-gap discharge), ±4kV (Contact discharge)

**Connections**

Input Ports	2 x HDMI input [Type A, 19-pin female]
Output Ports	1 x HDMI output [Type A, 19-pin female] 1 x L/R audio output [3.5mm Stereo Mini-jack] 1 x RS-232 [3pin-3.81mm phoenix connector]
Control Ports	1 x IR EXT [3.5mm Stereo Mini-jack] 2 x USB HOST [USB Type B] 4 x USB DEVICES [USB Type A]

**Mechanical**

Housing	Metal Enclosure
Color	Black
Dimensions	175mm [W] x 100mm [D] x 30mm [H]
Weight	506g
Power Supply	Input: AC100 - 240V 50/60Hz Output: DC 12V/1A (US/EU standard, CE/FCC/UL certified)
Power Consumption	Typical value: 5.16W Standby mode: 0.6W
Operation Temperature	32 - 104°F / 0 - 40°C
Storage temperature	-4 - 140°F / -20 - 60°C
Relative Humidity	20 - 90% RH (no-condensing)

**Recommended HDMI Cable**

Video Resolution	4K60 4:4:4	1080P 4:4:4
HDMI Cable Type	HDMI Cable	HDMI Cable
HDMI Cable Length	5m/16ft	10m/33ft

The use of "Premium High Speed HDMI" cable is highly recommended.