

# SW-44-MV

4x4 HDMI 4K 18 Gbps Matrix /w Multi viewer

## FEATURE:

- HDCP 2.2 compliant
- Support video resolution up to 4K@60Hz 4:4:4 and 18Gbps video bandwidth, as specified in HDMI 2.0
- Support 12 display categories in multi-viewer mode, and 9 splicing modes in video wall mode
- HDMI audio format: LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTSEX, DTS-96/24, DTS High Res, DTS-HD Master Audio
- Support CEC control, and multiple video resolution output
- Advanced EDID management
- Control via front panel buttons, IR remote, RS-232, and Web GUI



## SW-44-MV

The 18Gbps 4x4 Seamless Matrix provides an ideal solution for routing video from four HDMI sources to four HDTV displays. It features video wall and multi-viewer capabilities with various display modes, and supports 4x4 IR matrix functionality, as well as audio embedding and de-embedding. The matrix handles video resolutions up to 4K@60Hz 4:4:4, with each source capable of independent scaling. Seamless switching ensures smooth transitions between sources without frame loss. Control options include front panel buttons, IR remote, RS-232, and Web GUI.



## Switchers

4x4 HDMI 4K 18 Gbps Matrix w Multi viewer


**SW-44-MV** 4x4 HDMI 4K 18 Gbps Matrix /w Multi viewer

**SPECIFICATIONS:**
**Technical**

HDMI Compliance	HDMI 2.0
HDCP Compliance	HDCP 2.2
Video Bandwidth	594MHz/8Gbps
Video Resolution	480i -1080P@50/60Hz, 4K2K@24/30Hz, 4K2K@60Hz
Color Space	RGB, YCbCr 4:4:4, YCbCr 4:2:2, YCbCr 4:2:0
Color Depth	8/10/12-bit
Audio Formats	LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio
IR Level	12Vp-p
IR Frequency	Wideband 20K-60KHz
ESD Protection	Human body model — ±8kV (air-gap discharge) & ±4kV (contact discharge)

**Connections**

Input ports	4x HDMI Type A [19-pin female] 4x L/R AUDIO INPUT [3.81mm, 3pin Phoenix Connector]
Output ports	4x HDMI Type A [19-pin female] 4 × OPTICAL AUDIO OUT [S/PDIF] 4 × L/R AUDIO OUT [3.81mm, 5pin Phoenix Connector]
Control ports	1x TCP/IP [RJ45] 1 × RS-232 [D-Sub 9] 1x IR EXT [3.5mm Stereo Mini-jack] 4 × IR INPUT [3.5mm, Stereo Mini-jack] 4 × IR OUTPUT [3.5mm, Stereo Mini-jack]

**Mechanical**

Housing	Metal Enclosure												
Color	Black												
Dimensions	440mm [W]x203mm [D]x44.5mm [H]												
Weight	2.55kg												
Power Supply	Input: AC 100-240V 50/60Hz Output: DC 12V/2.5A (US/EU standard, CE/FCC/UL certified)												
Power Consumption	25W (max)												
Operation Temperature	32 - 104°F / 0 - 40°C												
Storage temperature	-4 - 140°F / -20 - 60°C												
Relative Humidity	20 - 90% RH (no condensation)												
Resolution / Cable length	<table border="0"> <tr> <td>4K60</td> <td>4K30</td> <td>1080P60</td> </tr> <tr> <td>- Feet / Meters</td> <td>- Feet / Meters</td> <td>- Feet / Meters</td> </tr> <tr> <td>HDMI IN / OUT</td> <td>16ft / 5M</td> <td>32ft / 10M</td> </tr> <tr> <td></td> <td></td> <td>50ft / 15M</td> </tr> </table>	4K60	4K30	1080P60	- Feet / Meters	- Feet / Meters	- Feet / Meters	HDMI IN / OUT	16ft / 5M	32ft / 10M			50ft / 15M
4K60	4K30	1080P60											
- Feet / Meters	- Feet / Meters	- Feet / Meters											
HDMI IN / OUT	16ft / 5M	32ft / 10M											
		50ft / 15M											
The use of "Premium High Speed HDMI" cable is highly recommended.													

**Certification**

Unit	CC, FCC
------	---------